



ZEBRA CS4070-HC

THE POCKET-SIZED WIRELESS ENTERPRISE-CLASS 1D/2D SCANNER FOR CARTS AND MORE.

Put advanced bar code scanning in the pockets of your healthcare workers to improve patient safety and the patient experience.

Bar code scanning at patient bedside is crucial in preventing deadly errors in medication administration and specimen collection. Now, you can keep enterprise-class bar code capture at the fingertips of every nurse and lab technician with the CS4070-HC. This little wireless enterprise class bar code scanner is designed for the mission critical world of the healthcare worker. Small enough to be easily carried at all times, it can be tucked in a pocket or worn on a lanyard. Superior scanning technology means your healthcare workers can dependably scan any electronic or printed 1-D or 2-D bar code in any condition in the time it takes to press the scan button, whenever and wherever required. With the press of the dedicated pairing button, this flexible Bluetooth scanner is easily paired with in-room computers and workstations-on-wheels (WOWs) — or even tablets. Add its rugged disinfectant-ready design that prevents the spread of germs, full shift power, user-selectable scanning feedback and superior ergonomics, and the CS4070-HC is the ideal individual scanning companion for your healthcare workers.

PRZM Intelligent Imaging technology for next generation bar code scanning performance — only from Zebra

Delivers laser-style speed and accuracy for first-time every time split second capture of 1D and 2D printed bar codes in virtually any condition — even if they are dirty, scratched or poorly printed.

Scan virtually any bar code on any medium

Scans 1-D, 2-D and PDF417 bar codes displayed on a screen or printed on paper labels, as well as the tiny bar codes printed on individual medication doses and bar codes on curved, reflective surfaces, such as vials, syringes, IV bags, suppositories and patient wristbands.

Superior ergonomics

One of the smallest and lightest devices in its class, the CS4070-HC can be tucked in a pocket or worn around the neck on a lanyard. Grooves guide the hand to the most comfortable placement and provide a secure grip, and the placement of trigger buttons enables effortless scanning with any size hand.

Connect with one simple scan

Healthcare workers can connect the CS4070-HC to a workstation-on-wheels (WOW) or thin client by simply scanning a barcode on the CS4070-HC Bluetooth dongle accessory.

Withstands constant disinfecting

IP52 sealing and a specially designed disinfectant-ready plastic housing allow safe wipe-down with a wide variety of harsh chemicals to help prevent the spread of germs.

Durable design — built to be dropped

Operates reliably after 5 ft./1.2 m drops and 500 consecutive “tumbles” from 1.64 ft./0.5 m.

APPLICATIONS

- Medication administration
- Blood product administration
- Specimen labeling
- Specimen tracking
- Medication tracking at the dose level in the hospital pharmacy
- Inventory takes in individual floor supply cabinets for timely replenishment

One million+ scans for superior value

Since healthcare workers need to scan frequently, the scan button is tested to handle over a million presses.

Full-shift power — period

In the mission-critical world of healthcare, users count on full-shift operation. That's why the field replaceable battery can be easily changed on-the-go and is designed to last an entire busy 12-hour shift, with an LED indicator that alerts the user when a battery change is needed.

Day and night 'do-not-disturb' modes

Healthcare workers can choose to mix and match the decode feedback that is right for the moment: visual (green light/red light), haptic (vibration) and an audible tone.

Point-and-shoot scanning simplicity

Bar code capture is easy. An extraordinarily wide working range combined with omnidirectional scanning eliminates the need to align scanner and bar code — no need to disturb a sleeping patient to capture the bar code on a wristband.

With Service from the Start Advance Exchange with Comprehensive Coverage, your CS4070-HC scanners are covered — period.

This optional service plan keeps devices up, running and in like-new condition with coverage for accidental damage and everyday wear-and-tear — all for just pennies a day.

GIVE YOUR HEALTHCARE WORKERS THE POCKETABLE 1D/2D BAR CODE SCANNING THEY NEED TO IMPROVE PATIENT SAFETY- AND THE PATIENT EXPERIENCE.

For more information, visit www.zebra.com/cs4070hc or access our global contact directory at www.zebra.com/contact

CS4070-HC SPECIFICATIONS CHART

PHYSICAL CHARACTERISTICS		USER ENVIRONMENT (CONTINUED)	
Dimensions	4.39 in. L x 1.79 in. W x 1.02 in. H 11.15 cm L x 4.55 cm W x 2.6 cm H	Ambient Lighting Tolerance	Tolerant to typical artificial indoor and natural outdoor (direct sunlight) lighting conditions. Fluorescent, Incandescent, Mercury Vapor, Sodium Vapor, LED1: 450 ft. candles (4,844 Lux) Sunlight: 8,000 ft. candles (86,111 Lux)
Weight	With batteries: 3.28 oz./93.2 g		
Scan Engine	SE4710 image engine		
Memory	512 MB Flash		
Memory Capacity	Over 1 million barcodes (UPC with time date stamp)		
LEDs	Scan LED (Green, Red, and Amber) and Bluetooth® LED (Blue) Four LED battery status indicator	BLUETOOTH	
Buttons	Scan, remove scan (batch mode only), enable Bluetooth (RF scanners only), battery status; scan button tested to a million depressions, all other buttons tested to 250,000 depressions	Bluetooth Radio	Bluetooth, Class 1/Class 2, Version 2.1 + Enhanced Data Rate (EDR)
		Bluetooth Range	300 ft./100 m when configured for Class 1 or 30 ft./10 m when configured for Class 2
		Bluetooth Profiles	HID keyboard wedge and Serial Port Profile (SPP) and Wireless SS I (proprietary)
OPERATING MODES		ACCESSORIES	

Scans recorded with optional time/
date stamp

Open Bluetooth Real time wireless data
transmission

BATTERY

Battery 950 mAh Lithium ion

Charge Time 3 hours 40 minutes

Battery Life Batch: 24 hours use or 8,500
scans
(6 scans per minute on full charge)
Standby: 3 months Bluetooth
12 hours use or 4,250 scans
(6 scans per minute on full charge)

IEC62471:2006 (Ed.1.0); EN62471
:2008 (LED)

EMC FCC Part 15 Class B, ICES 003
Class B,
EN 55022, EN 55024, EN 301 489-
1,
EN 301 489-17

Power Consumption 5V, 500mA max while charging

Radio EN 300 328

PERFORMANCE CHARACTERISTICS

Decode Capability 1D and 2D symbologies

Interfaces Supported USB (micro jack): Bluetooth

Real Time Clock A date/time stamp can be recorded
with each bar code scanned (batch
mode operation only)

Batch Communication USB 2.0

Electrical Safety UL 60950-1, C22.2 No. 60950-1,
EN 60950-1,
IEC 60950-1

Environmental EN50581

WARRANTY

Warranted against defects in workmanship and materials
for a period of thirty-six (36) months

USER ENVIRONMENT

Drop Specification Multiple 5 ft./1.5 m drops to
concrete

Tumble Specification 250 cycles @ 1.64 ft./0.5 m (500
drops)

Sealing IP52, disinfectant ready

Operating Temperature 32° to 104° F/0° to 40° C

Storage Temperature -40° to 158° F/-40° to 70°C

Humidity 10 to 95% noncondensing

DECODE RANGE

4 mil Code 39: 2.9 in. / 7.4 cm — 8.4 in. / 21.4 cm

5 mil Code 128: 2.4 in. / 6.1 cm — 7.8 in. / 19.8 cm

5 mil 39: 1.6 in. / 4.1 cm — 13.1 in. / 33.3
cm

5 mil PDF417: 2.7 in. / 6.9 cm — 8.0 in. / 20.3 cm

10 mil Data Matrix: 2.5 in. / 6.4 cm — 9.7 in. / 24.7 cm

100% UPCA: 1.4 in. / 3.6 cm* — 25.6 in. / 65.0
cm

20.0 mil Code 39: 1.6 in. / 4.1 cm* — 29.6 in. / 75.2
cm

*Minimum distance determined by symbol length and
scan angle

SERVICES

Enjoy easy access to fast repair and expert support with
Service from the Start. Add “next business day”
replacement with Advanced Exchange.



TCG, LLC
17400 Falls Rd
Upperco, MD 21155
P: 410-239-6808
F: 410-374-1245
E: Sales@tcg-llc.net